



• In addition to routine checks for each use, PPE should regularly undergo a detailed inspection by a competent person. Petzl recommends an inspection every 12 months and after any exceptional event in the life of the product

• PPE inspection should be conducted with the manufacturer's Instructions for Use.

Download the instructions at PETZL.COM.

				\sim
_			-v	
	w	-	- 1	

User information PPE information Surname Model Address Serial number Year of manufacture Date of purchase Identifier Date of first use

Manufacturer: Petzl, ZI Cidex 105A - 38920 Crolles - France



1. Known product history

Usage conditions or exceptional event during use (examples: fall or fall arrest, use or storage at extreme temperatures, modification outside manufacturer's facilities...):



2. Preliminary observations

Verify the presence and legibility of the serial number and the CE mark. Verify that the product lifetime has not been exceeded.

Compare with a new device to verify there are no modifications or missing elements.

3. Checking the general condition

- Check the condition of the side plates (marks, deformation, cracks, corrosion, wear...)
- Check the condition of the attachment holes (marks, deformation, cracks, corrosion...).
- For pulleys with moving side plates, verify that the side plates rotate properly.
- Check the condition of the rivets (marks, deformation, cracks, corrosion, absence of play...)

4. Checking the condition of the sheave

- Check the condition of the sheave (marks, deformation, corrosion, absence of foreign bodies...).
- Verify that the sheave turns freely.

5. Function check

- Install your pulley on an anchor and install a compatible rope around the sheave.
- Circulate the rope in both directions

Comments (detail here any defects found on the product and accomplished tasks)

VERDICT Product fit to remain in service Product unfit to remain in service

Inspected by Company Date Next inspection date